

## Technical Data Chamber Furnaces

### Chamber Furnaces KM 10/13

<b>Max. temperature:</b>	<b>1300°C</b>
<b>Inside dimensions (mm):</b>	<b>W 250 x D 250 x H 120</b>
<b>Outside dimensions (mm):</b>	<b>W 500 x D 600 x H 700</b>
<b>Weight:</b>	<b>69 kg</b>
<b>Volume:</b>	<b>8 l</b>
<b>Power:</b>	<b>2,5 kW</b>
<b>Voltage:</b>	<b>230 1/N V</b>

### Chamber Furnaces KM 15/13

<b>Max. temperature:</b>	<b>1300°C</b>
<b>Inside dimensions (mm):</b>	<b>W 250 x D 250 x H 200</b>
<b>Outside dimensions (mm):</b>	<b>W 500 x D 700 x H 700</b>
<b>Weight:</b>	<b>75 kg</b>
<b>Volume:</b>	<b>13 l</b>
<b>Power:</b>	<b>3,6 kW</b>
<b>Voltage:</b>	<b>230 1/N V</b>

### Chamber Furnaces KM 20/13

<b>Max. temperature:</b>	<b>1300°C</b>
<b>Inside dimensions (mm):</b>	<b>W 250 x D 350 x H 200</b>
<b>Outside dimensions (mm):</b>	<b>W 500 x D 700 x H 700</b>
<b>Weight:</b>	<b>91 kg</b>
<b>Volume:</b>	<b>18 l</b>
<b>Power:</b>	<b>6,0 kW</b>
<b>Voltage:</b>	<b>400 3/N V</b>

### Chamber Furnaces KM 30/13

<b>Max. temperature:</b>	<b>1300°C</b>
<b>Inside dimensions (mm):</b>	<b>W 250 x D 500 x H 200</b>
<b>Outside dimensions (mm):</b>	<b>W 500 x D 850 x H 700</b>
<b>Weight:</b>	<b>105 kg</b>
<b>Volume:</b>	<b>30 l</b>
<b>Power:</b>	<b>7,0 kW</b>
<b>Voltage:</b>	<b>400 3/N V</b>

### Chamber Furnaces KM 50/13

<b>Max. temperature:</b>	<b>1300°C</b>
<b>Inside dimensions (mm):</b>	<b>W 350 x D 500 x H 250</b>
<b>Outside dimensions (mm):</b>	<b>W 950 x D 1500 x H 1490</b>
<b>Weight:</b>	<b>268 kg</b>
<b>Volume:</b>	<b>44 l</b>
<b>Power:</b>	<b>13,0 kW</b>
<b>Voltage:</b>	<b>400 3/N V</b>

### Chamber Furnaces KM 70/13

<b>Max. temperature:</b>	<b>1300°C</b>
<b>Inside dimensions (mm):</b>	<b>W 350 x D 750 x H 250</b>
<b>Outside dimensions (mm):</b>	<b>W 950 x D 1500 x H 1740</b>
<b>Weight:</b>	<b>330 kg</b>
<b>Volume:</b>	<b>66 l</b>
<b>Power:</b>	<b>20 kW</b>
<b>Voltage:</b>	<b>400 3/N V</b>