

## Technical Data High Temperature with SiC up to 1500°C

### High Temperature Furnaces KLC 05/15

**Max. temperature:** 1500°C  
**Inside dimensions (mm):** W 150 x D 250 x H 140  
**Volume:** 5,3 l  
**Outside dimensions (mm):** W 550 x D 580 x H 650  
**Power:** 4,8 kW  
**Voltage:** 400 3/N V

### High Temperature Furnaces KLC 10/15

**Max. temperature:** 1500°C  
**Inside dimensions (mm):** W 200 x D 250 x H 180  
**Volume:** 9,0 l  
**Outside dimensions (mm):** W 560 x D 640 x H 720  
**Power:** 6,6 kW  
**Voltage:** 400 3/N V

### High Temperature Furnaces KLC 15/15

**Max. temperature:** 1500°C  
**Inside dimensions (mm):** W 220 x D 310 x H 220  
**Volume:** 15,0 l  
**Outside dimensions (mm):** W 590 x D 690 x H 790  
**Power:** 7,0 kW  
**Voltage:** 400 3/N V

### High Temperature Furnaces KLC 30/15

**Max. temperature:** 1500°C  
**Inside dimensions (mm):** W 250 x D 440 x H 270  
**Volume:** 29,7 l  
**Outside dimensions (mm):** W 660 x D 730 x H 800  
**Power:** 11,5 kW  
**Voltage:** 400 3/N V