

## Technical Data Air Circulating Chamber Furnaces up to 1000l

### Air Circulating Chamber Furnaces KU 40/04/A

Max. temperature:	450°C
Inside dimensions (mm):	W 300 x D 400 x H 300
Outside dimensions (mm):	W 570 x D 1050 x H 1270
Weight:	115 kg
Volume:	35 l
Power:	3,2 kW
Voltage:	400 3/N V

### Air Circulating Chamber Furnaces KU 70/04/A

Max. temperature:	450°C
Inside dimensions (mm):	W 350 x D 500 x H 400
Outside dimensions (mm):	W 620 x D 1150 x H 1370
Weight:	130 kg
Volume:	70 l
Power:	6,4 kW
Voltage:	400 3/N V

### Air Circulating Chamber Furnaces KU 140/04/A

Max. temperature:	450°C
Inside dimensions (mm):	W 450 x D 600 x H 500
Outside dimensions (mm):	W 720 x D 1250 x H 1470
Weight:	205 kg
Volume:	135 l
Power:	9,6 kW
Voltage:	400 3/N V

### Air Circulating Chamber Furnaces KU 270/04/A

Max. temperature:	450°C
Inside dimensions (mm):	W 600 x D 750 x H 600
Outside dimensions (mm):	W 870 x D 1450 x H 1620
Weight:	370 kg
Volume:	270 l
Power:	12,8 kW
Voltage:	400 3/N V

### Air Circulating Chamber Furnaces KU 540/04/A

Max. temperature:	450°C
Inside dimensions (mm):	W 750 x D 900 x H 800
Outside dimensions (mm):	W 1020 x D 1600 x H 1820
Weight:	540 kg
Volume:	540 l
Power:	19,2 kW
Voltage:	400 3/N V

### Air Circulating Chamber Furnaces KU 800/04/A

Max. temperature:	450°C
Inside dimensions (mm):	W 800 x D 1250 x H 800
Outside dimensions (mm):	W 1050 x D 1900 x H 1820
Weight:	850 kg
Volume:	800 l
Power:	24,0 kW
Voltage:	400 3/N V