

Technical Data Air Circulating Chamber Furnaces up to 1000l

Air Circulating Chamber Furnaces KU 40/08/A

Max. temperature:	850°C
Inside dimensions (mm):	W 300 x D 400 x H 300
Outside dimensions (mm):	W 850 x D 1360 x H 1470
Weight:	290 kg
Volume:	35 l
Power:	6,0 kW
Voltage:	400 3/N V

Air Circulating Chamber Furnaces KU 70/08/A

Max. temperature:	850°C
Inside dimensions (mm):	W 350 x D 500 x H 400
Outside dimensions (mm):	W 900 x D 1460 x H 1570
Weight:	360 kg
Volume:	70 l
Power:	9,0 kW
Voltage:	400 3/N V

Air Circulating Chamber Furnaces KU 140/08/A

Max. temperature:	850°C
Inside dimensions (mm):	W 450 x D 600 x H 500
Outside dimensions (mm):	W 1000 x D 1560 x H 1670
Weight:	580 kg
Volume:	135 l
Power:	15,0 kW
Voltage:	400 3/N V

Air Circulating Chamber Furnaces KU 270/08/A

Max. temperature:	850°C
Inside dimensions (mm):	W 600 x D 750 x H 600
Outside dimensions (mm):	W 1150 x W 1710 x H 1770
Weight:	770 kg
Volume:	270 l
Power:	20,0 kW
Voltage:	400 3/N V

Air Circulating Chamber Furnaces KU 540/08/A

Max. temperature:	850°C
Inside dimensions (mm):	W 750 x D 900 x H 800
Outside dimensions (mm):	W 1330 x D 1910 x H 2125
Weight:	970 kg
Volume:	540 l
Power:	30,0 kW
Voltage:	400 3/N V

Air Circulating Chamber Furnaces KU 800/08/A

Max. temperature:	850°C
Inside dimensions (mm):	W 800 x D 1250 x H 800
Outside dimensions (mm):	W 1380 x D 2260 x H 2125
Weight:	1340 kg
Volume:	800 l
Power:	40,0 kW
Voltage:	400 3/N V