

## Technical Data Air Circulation Bogie-Hearth Furnaces

### Air Circulation Bogie-Hearth Furnaces WM 1000/08/A

Max. temperature:	850°C
Inside dimensions (mm):	W 1000 x D 1000 x H 1000
Outside dimensions (mm):	W 2200 x D 1800 x H 3200
Weight:	1420 kg
Volume:	1000 l
Power:	50,0 kW
Voltage:	400 3/N V

### Air Circulation Bogie-Hearth Furnaces WM 1500/08/A

Max. temperature:	850°C
Inside dimensions (mm):	W 1000 x D 1500 x H 1000
Outside dimensions (mm):	W 2200 x D 2300 x H 3200
Weight:	1570 kg
Volume:	1500 l
Power:	66,0 kW
Voltage:	400 3/N V

### Air Circulation Bogie-Hearth Furnaces WM 2000/08/A

Max. temperature:	850°C
Inside dimensions (mm):	W 1000 x D 2000 x H 1000
Outside dimensions (mm):	W 2200 x D 2900 x H 3200
Weight:	1950 kg
Volume:	2000 l
Power:	86,0 kW
Voltage:	400 3/N V

### Air Circulation Bogie-Hearth Furnaces WM 3500/08/A

Max. temperature:	850°C
Inside dimensions (mm):	W 1300 x D 2500 x H 1100
Outside dimensions (mm):	W 2500 x D 3100 x H 3500
Weight:	2400 kg
Volume:	3580 l
Power:	101,0 kW
Voltage:	400 3/N V

### Air Circulation Bogie-Hearth Furnaces WM 5000/08/A

Max. temperature:	850°C
Inside dimensions (mm):	W 1300 x D 3100 x H 1250
Outside dimensions (mm):	W 2500 x D 3800 x H 3700
Weight:	4600 kg
Volume:	5040 l
Power:	156,0 kW
Voltage:	400 3/N V

Air Circulation Bogie-Hearth Furnaces WM 7200/08/A

Max. temperature:	850°C
Inside dimensions (mm):	W 1500 x D 3100 x H 1500
Outside dimensions (mm):	W 2800 x D 3800 x H 3900
Weight:	5300 kg
Volume:	6980 l
Power:	168,0 kW
Voltage:	400 3/N V