

Technical Data Ashing Furnaces up to 1100°C

Ashing Furnaces KLS 05/11/ASH

Max. temperature: 1100°C
Inside dimensions (mm): W 200 x D 250 x H 140
Volume: 7 l
Outside dimensions (mm): W 550 x D 580 x H 650
Power: 2,0 kW
Voltage: 230 1/N V

Ashing Furnaces KLS 10/11/ASH

Max. temperature: 1100°C
Inside dimensions (mm): W 200 x D 250 x H 200
Volume: 10 l
Outside dimensions (mm): W 560 x D 640 x H 720
Power: 3,6 kW
Voltage: 230 1/N V

Ashing Furnaces KLS 15/11/ASH

Max. temperature: 1100°C
Inside dimensions (mm): W 220 x D 300 x H 230
Volume: 15 l
Outside dimensions (mm): W 560 x D 640 x H 720
Power: 3,6 kW
Voltage: 230 1/N V

Ashing Furnaces KLS 30/11/ASH

Max. temperature: 1100°C
Inside dimensions (mm): W 280 x D 380 x H 280
Volume: 30 l
Outside dimensions (mm): W 590 x D 690 x H 790
Power: 6,0 kW
Voltage: 400 3/N V

Ashing Furnaces KLS 45/11/ASH

Max. temperature: 1100°C
Inside dimensions (mm): W 300 x D 500 x H 300
Volume: 45 l
Outside dimensions (mm): W 660 x D 810 x H 820
Power: 7,5 kW
Voltage: 400 3/N V

Ashing Furnaces KLS 60/11/ASH

Max. temperature:	1100°C
Inside dimensions (mm):	W 400 x D 500 x H 300
Volume:	60 l
Outside dimensions (mm):	W 760 x D 840 x H 800
Power:	9,6 kW
Voltage:	400 3/N V