

Technical Data Chamber Furnaces Cubic Furnace Chamber

Chamber Furnaces KC 16/13

Max. temperature:	1300°C
Inside dimensions (mm):	W 250 x D 250 x H 250
Volume:	16 l
Outside dimensions (mm):	W 660 x D 870 x H 1360
Power:	6,0 kW
Voltage:	400 3/N V
Weight:	155 kg

Chamber Furnaces KC 32/13

Max. temperature:	1300°C
Inside dimensions (mm):	W 320 x D 320 x H 320
Volume:	32 l
Outside dimensions (mm):	W 730 x D 940 x H 1430
Power:	8,0 kW
Voltage:	400 3/N V
Weight:	185 kg

Chamber Furnaces KC 64/13

Max. temperature:	1300°C
Inside dimensions (mm):	W 400 x D 400 x H 400
Volume:	64 l
Outside dimensions (mm):	W 810 x D 1020 x H 1510
Power:	10,0 kW
Voltage:	400 3/N V
Weight:	255 kg

Chamber Furnaces KC 128/13

Max. temperature:	1300°C
Inside dimensions (mm):	W 500 x D 500 x H 500
Volume:	128 l
Outside dimensions (mm):	W 910 x D 1120 x H 1610
Power:	12,0 kW
Voltage:	400 3/N V
Weight:	320 kg

Chamber Furnaces KC 220/13

Max. temperature:	1300°C
Inside dimensions (mm):	W 600 x D 600 x H 600
Volume:	216 l
Outside dimensions (mm):	W 1010 x D 1220 x H 1710
Power:	20,0 kW
Voltage:	400 3/N V
Weight:	410 kg

Chamber Furnaces KC 520/13

Max. temperature: 1300°C
Inside dimensions (mm): W 800 x D 800 x H 800
Volume: 512 l
Outside dimensions (mm): W 1210 x D 1420 x H 1910
Power: 48,0 kW
Voltage: 400 3/N V
Weight: 730 kg

Chamber Furnaces KC 1000/13

Max. temperature: 1300°C
Inside dimensions (mm): W 1000 x D 1000 x H 1000
Volume: 1000 l
Outside dimensions (mm): W 1640 x D 1840 x H 1970
Power: 76,0 kW
Voltage: 400 3/N V
Weight: 1480 kg

Chamber Furnaces KC 2000/13

Max. temperature: 1300°C
Inside dimensions (mm): W 1250 x D 1250 x H 1250
Volume: 1950 l
Outside dimensions (mm): W 1890 x D 2090 x H 2220
Power: 140,0 kW
Voltage: 400 3/N V
Weight: 2780 kg