

Technical Data Chamber Furnaces

Chamber Furnaces KK 100/09../12

Max. temperature:	900°C, 1280°C
Inside dimensions (mm):	W 410 x D 470 x H 540
Volume:	100 l
Outside dimensions (mm):	W 750 x D 970 x H 1640
Power:	6,6/8 kW
Voltage:	400 3/N V
Weight:	320 kg

Chamber Furnaces KK 150/09../12

Max. temperature:	900°C, 1280°C
Inside dimensions (mm):	W 460 x D 470 x H 690
Volume:	150 l
Outside dimensions (mm):	W 800 x D 970 x H 1730
Power:	9/10,5 kW
Voltage:	400 3/N V
Weight:	430 kg

Chamber Furnaces KK 200/09../12

Max. temperature:	900°C, 1280°C
Inside dimensions (mm):	W 460 x D 630 x H 690
Volume:	200 l
Outside dimensions (mm):	W 800 x D 1100 x H 1730
Power:	11/13,2 kW
Voltage:	400 3/N V
Weight:	460 kg

Chamber Furnaces KK 250/09../12

Max. temperature:	900°C, 1280°C
Inside dimensions (mm):	W 520 x D 630 x H 770
Volume:	250 l
Outside dimensions (mm):	W 860 x D 1110 x H 1750
Power:	13,5/16,5 kW
Voltage:	400 3/N V
Weight:	480kg

Chamber Furnaces KK 330/09../12

Max. temperature:	900°C, 1280°C
Inside dimensions (mm):	W 580 x D 710 x H 800
Volume:	330 l
Outside dimensions (mm):	W 920 x D 1190 x H 1750
Power:	16,5/22 kW
Voltage:	400 3/N V
Weight:	530 kg

Chamber Furnaces KK 480/09../12

Max. temperature: 900°C, 1280°C
Inside dimensions (mm): W 550 x D 800 x H 800
Volume: 480 l
Outside dimensions (mm): W 970 x D 1250 x H 1760
Power: 32 kW
Voltage: 400 3/N V
Weight: 620 kg

Chamber Furnaces KK 600/09../12

Max. temperature: 900°C, 1280°C
Inside dimensions (mm): W 710 x D 820 x H 1030
Volume: 600 l
Outside dimensions (mm): W 1050 x D 1300 x H 1770
Power: 40 kW
Voltage: 400 3/N V
Weight: 730 kg

Chamber Furnaces KK 750/09../12

Max. temperature: 900°C, 1280°C
Inside dimensions (mm): W 710 x D 1020 x H 1030
Volume: 740 l
Outside dimensions (mm): W 1050 x D 1500 x H 1770
Power: 50 kW
Voltage: 400 3/N V
Weight: 780 kg

Chamber Furnaces KK 1000/09../12

Max. temperature: 900°C, 1280°C
Inside dimensions (mm): W 910 x D 1005 x H 1145
Volume: 1060 l
Outside dimensions (mm): W 1250 x D 1490 x H 1890
Power: 70 kW
Voltage: 400 3/N V
Weight: 1150 kg

Chamber Furnaces KK 1500/09../12

Max. temperature: 900°C, 1280°C
Inside dimensions (mm): W 900 x D 1200 x H 1400
Volume: 1510 l
Outside dimensions (mm): W 1590 x D 2090 x H 2410
Power: 58/76 kW
Voltage: 400 3/N V
Weight: 2250 kg

Chamber Furnaces KK 2000/09../12

Max. temperature: 900°C, 1280°C
Inside dimensions (mm): W 1000 x D 1300 x H 1500
Volume: 1950 l
Outside dimensions (mm): W 1690 x D 2190 x H 2510
Power: 76/110 kW
Voltage: 400 3/N V
Weight: 2890 kg

Chamber Furnaces KK 2500/09../12

Max. temperature: 900°C, 1280°C
Inside dimensions (mm): W 1000 x D 1500 x H 1650
Volume: 2480 l
Outside dimensions (mm): W 1690 x D 2390 x H 2660
Power: 110/140 kW
Voltage: 400 3/N V
Weight: 3000 kg