

Technical Data Combi Furnaces up to 1400

Combi Furnaces KK 150/12 DB

Max. temperature: 1280°C
Inside dimensions (mm): W 430 x D 520 x H 640
Volume: 145 l
Outside dimensions (mm): W 940 x D 1150 x H 1750
Power: 23,0 kW
Voltage: 400 3/N V

Combi Furnaces KK 250/12 DB

Max. temperature: 1280°C
Inside dimensions (mm): W 430 x D 660 x H 760
Volume: 215 l
Outside dimensions (mm): W 940 x D 1290 x H 1870
Power: 27,0 kW
Voltage: 400 3/N V

Combi Furnaces KK 350/12 DB

Max. temperature: 1280°C
Inside dimensions (mm): W 480 x D 800 x H 800
Volume: 310 l
Outside dimensions (mm): W 960 x D 1430 x H 1910
Power: 42,0 kW
Voltage: 400 3/N V

Combi Furnaces KK 500/12 DB

Max. temperature: 1280°C
Inside dimensions (mm): W 580 x D 780 x H 1000
Volume: 450 l
Outside dimensions (mm): W 1340 x D 1670 x H 2010
Power: 54,0 kW
Voltage: 400 3/N V

Combi Furnaces KK 150/13 DB

Max. temperature: 1340°C
Inside dimensions (mm): W 430 x D 520 x H 640
Volume: 145 l
Outside dimensions (mm): W 940 x D 1150 x H 1750
Power: 23,0 kW
Voltage: 400 3/N V

Combi Furnaces KK 250/13 DB

Max. temperature: 1340°C
Inside dimensions (mm): W 430 x D 660 x H 760
Volume: 215 l
Outside dimensions (mm): W 940 x D 1290 x H 1870
Power: 27,0 kW
Voltage: 400 3/N V

Combi Furnaces KK 350/13 DB

Max. temperature: 1340°C
Inside dimensions (mm): W 480 x D 800 x H 800
Volume: 310 l
Outside dimensions (mm): W 960 x D 1430 x H 1910
Power: 42,0 kW
Voltage: 400 3/N V

Combi Furnaces KK 500/13 DB

Max. temperature: 1340°C
Inside dimensions (mm): W 580 x D 780 x H 1000
Volume: 450 l
Outside dimensions (mm): W 1340 x D 1670 x H 2010
Power: 54,0 kW
Voltage: 400 3/N V

Combi Furnaces KK 150/14 DB

Max. temperature: 1400°C
Inside dimensions (mm): W 430 x D 520 x H 640
Volume: 145 l
Outside dimensions (mm): W 940 x D 1150 x H 1750
Power: 23,0 kW
Voltage: 400 3/N V

Combi Furnaces KK 250/14 DB

Max. temperature: 1400°C
Inside dimensions (mm): W 430 x D 660 x H 760
Volume: 215 l
Outside dimensions (mm): W 940 x D 1290 x H 1870
Power: 27,0 kW
Voltage: 400 3/N V

Combi Furnaces KK 350/14 DB

Max. temperature: 1400°C
Inside dimensions (mm): W 480 x D 800 x H 800
Volume: 310 l
Outside dimensions (mm): W 960 x D 1430 x H 1910
Power: 42,0 kW
Voltage: 400 3/N V

Combi Furnaces KK 500/14 DB

Max. temperature: 1400°C
Inside dimensions (mm): W 580 x D 780 x H 1000
Volume: 450 l
Outside dimensions (mm): W 1340 x D 1670 x H 2010
Power: 54,0 kW
Voltage: 400 3/N V