

Technical Data High Temperature Furnaces / Bench Top up to 1600°C

Hightemperature Furnaces HTL 02/16

Max. temperature:	1600°C
Inside dimensions (mm):	W 110 x D 120 x H 150
Volume:	2 l
Outside dimensions (mm):	W 740 x D 440 x H 630
Power:	1,5 kW
Voltage:	230 1/N V
Weight:	76 kg

Hightemperature Furnaces HTL 04/16

Max. temperature:	1600°C
Inside dimensions (mm):	W 150 x D 150 x H 150
Volume:	3,5 l
Outside dimensions (mm):	W 740 x D 440 x H 630
Power:	3,0 kW
Voltage:	230 1/N V
Weight:	83 kg

Hightemperature Furnaces HTL 10/16

Max. temperature:	1600°C
Inside dimensions (mm):	W 200 x D 250 x H 200
Volume:	10 l
Outside dimensions (mm):	W 790 x D 540 x H 680
Power:	4,0 kW
Voltage:	400 3/N V
Weight:	97 kg

Hightemperature Furnaces HTL 16/16

Max. temperature:	1600°C
Inside dimensions (mm):	W 200 x D 300 x H 2600
Volume:	15,6 l
Outside dimensions (mm):	W 830 x D 550 x H 735
Power:	8 kW
Voltage:	400 3/N V
Weight:	175 kg

Hightemperature Furnaces HTL 20/16

Max. temperature:	1600°C
Inside dimensions (mm):	W 250 x D 320 x H 260
Volume:	21 l
Outside dimensions (mm):	W 880 x D 570 x H 735
Power:	8 kW
Voltage:	400 3/N V
Weight:	210 kg