

## Technical Data High Temperature with SiC up to 1600°C

### High Temperature Furnaces KLC 05/16

Max. temperature: 1600°C  
Inside dimensions (mm): W 150 x D 250 x H 140  
Volume: 5,3 l  
Outside dimensions (mm): W 550 x D 580 x H 650  
Power: 5,2 kW  
Voltage: 400 3/N V

### High Temperature Furnaces KLC 10/16

Max. temperature: 1600°C  
Inside dimensions (mm): W 200 x D 250 x H 180  
Volume: 9,0 l  
Outside dimensions (mm): W 560 x D 640 x H 720  
Power: 6,9 kW  
Voltage: 400 3/N V

### High Temperature Furnaces KLC 15/16

Max. temperature: 1600°C  
Inside dimensions (mm): W 220 x D 310 x H 220  
Volume: 15,0 l  
Outside dimensions (mm): W 590 x D 690 x H 790  
Power: 7,0 kW  
Voltage: 400 3/N V

### High Temperature Furnaces KLC 30/16

Max. temperature: 1600°C  
Inside dimensions (mm): W 250 x D 440 x H 270  
Volume: 29,7 l  
Outside dimensions (mm): W 660 x D 730 x H 800  
Power: 11,5 kW  
Voltage: 400 3/N V