

## Technical Data Laboratory Chamber Furnaces up to 1200°C

### Chamber Furnaces KLS 05/12

Max. temperature:	1200°C
Inside dimensions (mm):	W 200 x D 250 x H 140
Volume:	7 l
Outside dimensions (mm):	W 550 x D 580 x H 650
Power:	2,0 kW
Voltage:	230 1/N V

### Chamber Furnaces KLS 10/12

Max. temperature:	1200°C
Inside dimensions (mm):	W 200 x D 250 x H 200
Volume:	10 l
Outside dimensions (mm):	W 560 x D 640 x H 720
Power:	3,6 kW
Voltage:	230 1/N V

### Chamber Furnaces KLS 15/12

Max. temperature:	1200°C
Inside dimensions (mm):	W 220 x D 300 x H 230
Volume:	15 l
Outside dimensions (mm):	W 560 x D 640 x H 720
Power:	3,6 kW
Voltage:	230 1/N V

### Chamber Furnaces KLS 30/12

Max. temperature:	1200°C
Inside dimensions (mm):	W 280 x D 380 x H 280
Volume:	30 l
Outside dimensions (mm):	W 590 x D 690 x H 790
Power:	6,0 kW
Voltage:	400 3/N V

### Chamber Furnaces KLS 45/12

Max. temperature:	1200°C
Inside dimensions (mm):	W 300 x D 500 x H 300
Volume:	45 l
Outside dimensions (mm):	W 660 x D 810 x H 820
Power:	7,5 kW
Voltage:	400 3/N V

## Chamber Furnaces KLS 60/12

Max. temperature:	1200°C
Inside dimensions (mm):	W 400 x D 500 x H 300
Volume:	60 l
Outside dimensions (mm):	W 760 x D 840 x H 800
Power:	9,6 kW
Voltage:	400 3/N V