

Technical Data Tube Furnaces up to 1200°C

Tube Furnaces ROT 60/300/12

Max. temperature:	1200°C
Heated length:	300 mm
Temp. const. zone:	100 mm
Max. Ø pipe intake:	≤ 60 mm
Power:	3,0 kW
Voltage:	230 1/N V

Tube Furnaces ROT 60/450/12

Max. temperature:	1200°C
Heated length:	450 mm
Temp. const. zone:	150 mm
Max. Ø pipe intake:	≤ 60 mm
Power:	3,6 kW
Voltage:	230 1/N V

Tube Furnaces ROT 60/600/12

Max. temperature:	1200°C
Heated length:	600 mm
Temp. const. zone:	200 mm
Max. Ø pipe intake:	≤ 60 mm
Power:	3,6 kW
Voltage:	230 1/N V

Tube Furnaces ROT 85/300/12

Max. temperature:	1200°C
Heated length:	300 mm
Temp. const. zone:	100 mm
Max. Ø pipe intake:	≤ 85 mm
Power:	3,0 kW
Voltage:	230 1/N V

Tube Furnaces ROT 85/450/12

Max. temperature:	1200°C
Heated length:	450 mm
Temp. const. zone:	150 mm
Max. Ø pipe intake:	≤ 85 mm
Power:	3,6 kW
Voltage:	230 1/N V

Tube Furnaces ROT 85/600/12

Max. temperature:	1200°C
Heated length:	600 mm
Temp. const. zone:	200 mm
Max. Ø pipe intake:	≤ 85 mm
Power:	3,6 kW
Voltage:	230 1/N V

Tube Furnaces ROT 120/300/12

Max. temperature:	1200°C
Heated length:	300 mm
Temp. const. zone:	100 mm
Max. Ø pipe intake:	≤ 120 mm
Power:	5,0 kW
Voltage:	400 3/N V

Tube Furnaces ROT 120/450/12

Max. temperature:	1200°C
Heated length:	450 mm
Temp. const. zone:	150 mm
Max. Ø pipe intake:	≤ 120 mm
Power:	5,0 kW
Voltage:	400 3/N V

Tube Furnaces ROT 120/600/12

Max. temperature:	1200°C
Heated length:	600 mm
Temp. const. zone:	200 mm
Max. Ø pipe intake:	≤ 120 mm
Power:	7,5 kW
Voltage:	400 3/N V