

## Technical Data Tube Furnaces up to 1400°C

### Tube Furnaces ROC 50/250/14

|                        |                       |
|------------------------|-----------------------|
| Max. temperature:      | 1400°C                |
| Heated length:         | 250 mm                |
| Temp. const. zone:     | 80 mm                 |
| Outer dimensions (mm): | W 665 x D 430 x H 750 |
| Inside-Ø:              | 50 mm                 |
| Power:                 | 3,0 kW                |
| Voltage:               | 400 3/N V             |

### Tube Furnaces ROC 50/450/14

|                        |                       |
|------------------------|-----------------------|
| Max. temperature:      | 1400°C                |
| Heated length:         | 450 mm                |
| Temp. const. zone:     | 150 mm                |
| Outer dimensions (mm): | W 850 x D 430 x H 750 |
| Inside-Ø:              | 50 mm                 |
| Power:                 | 4,0 kW                |
| Voltage:               | 400 3/N V             |

### Tube Furnaces ROC 50/610/14

|                        |                        |
|------------------------|------------------------|
| Max. temperature:      | 1400°C                 |
| Heated length:         | 610 mm                 |
| Temp. const. zone:     | 200 mm                 |
| Outer dimensions (mm): | W 1150 x D 430 x H 750 |
| Inside-Ø:              | 50 mm                  |
| Power:                 | 4,5 kW                 |
| Voltage:               | 400 3/N V              |

### Tube Furnaces ROC 75/450/14

|                        |                       |
|------------------------|-----------------------|
| Max. temperature:      | 1400°C                |
| Heated length:         | 450 mm                |
| Temp. const. zone:     | 150 mm                |
| Outer dimensions (mm): | W 850 x D 430 x H 750 |
| Inside-Ø:              | 75 mm                 |
| Power:                 | 5,5 kW                |
| Voltage:               | 400 3/N V             |

### Tube Furnaces ROC 75/610/14

|                        |                        |
|------------------------|------------------------|
| Max. temperature:      | 1400°C                 |
| Heated length:         | 610 mm                 |
| Temp. const. zone:     | 200 mm                 |
| Outer dimensions (mm): | W 1150 x D 430 x H 750 |
| Inside-Ø:              | 75 mm                  |
| Power:                 | 6,5 kW                 |
| Voltage:               | 400 3/N V              |

#### Tube Furnaces ROC 105/450/14

|                        |                       |
|------------------------|-----------------------|
| Max. temperature:      | 1400°C                |
| Heated length:         | 450 mm                |
| Temp. const. zone:     | 150 mm                |
| Outer dimensions (mm): | W 850 x D 470 x H 790 |
| Inside-Ø:              | 50 mm                 |
| Power:                 | 7,0 kW                |
| Voltage:               | 400 3/N V             |

#### Tube Furnaces ROC 105/610/14

|                        |                        |
|------------------------|------------------------|
| Max. temperature:      | 1400°C                 |
| Heated length:         | 610 mm                 |
| Temp. const. zone:     | 200 mm                 |
| Outer dimensions (mm): | W 1150 x D 470 x H 790 |
| Inside-Ø:              | 50 mm                  |
| Power:                 | 7,5 kW                 |
| Voltage:               | 400 3/N V              |