

Technical Data Tube Furnaces up to 1400°C

Tube Furnaces ROC 50/250/14

Max. temperature:	1400°C
Heated length:	250 mm
Temp. const. zone:	80 mm
Outer dimensions (mm):	W 665 x D 430 x H 750
Inside-Ø:	50 mm
Power:	3,0 kW
Voltage:	400 3/N V

Tube Furnaces ROC 50/450/14

Max. temperature:	1400°C
Heated length:	450 mm
Temp. const. zone:	150 mm
Outer dimensions (mm):	W 850 x D 430 x H 750
Inside-Ø:	50 mm
Power:	4,0 kW
Voltage:	400 3/N V

Tube Furnaces ROC 50/610/14

Max. temperature:	1400°C
Heated length:	610 mm
Temp. const. zone:	200 mm
Outer dimensions (mm):	W 1150 x D 430 x H 750
Inside-Ø:	50 mm
Power:	4,5 kW
Voltage:	400 3/N V

Tube Furnaces ROC 75/450/14

Max. temperature:	1400°C
Heated length:	450 mm
Temp. const. zone:	150 mm
Outer dimensions (mm):	W 850 x D 430 x H 750
Inside-Ø:	75 mm
Power:	5,5 kW
Voltage:	400 3/N V

Tube Furnaces ROC 75/610/14

Max. temperature:	1400°C
Heated length:	610 mm
Temp. const. zone:	200 mm
Outer dimensions (mm):	W 1150 x D 430 x H 750
Inside-Ø:	75 mm
Power:	6,5 kW
Voltage:	400 3/N V

Tube Furnaces ROC 105/450/14

Max. temperature:	1400°C
Heated length:	450 mm
Temp. const. zone:	150 mm
Outer dimensions (mm):	W 850 x D 470 x H 790
Inside-Ø:	50 mm
Power:	7,0 kW
Voltage:	400 3/N V

Tube Furnaces ROC 105/610/14

Max. temperature:	1400°C
Heated length:	610 mm
Temp. const. zone:	200 mm
Outer dimensions (mm):	W 1150 x D 470 x H 790
Inside-Ø:	50 mm
Power:	7,5 kW
Voltage:	400 3/N V